

1610~1650nm Polarization Beam Combiner/Splitter

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Optic Amplifiers
- Fiber Optic Instruments
- WDM Systems
- Dispersion Compensation
- Light Routing



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	1610, 1625, 1650	
Bandwidth	nm	+/-10	
Insertion Loss	(Typ.)	dB	0.7
	(Max.)	dB	0.9
Directivity	dB	≥50	
Optical Return Loss	dB	≥45	
Extinction Ratio (for FPBS)	(Typ.)	dB	23
	(Min.)	dB	20
Fiber Type of Port 1 & Port 2	-	PM1550 Panda Fiber or 10/125um PMSC Fiber (E) 10/125um PMDC Fiber (O), 12/130um PMDC Fiber (T) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1
Direction of Incident Polarization	-	Slow Axis	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(Ø)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN) FPBC=Polarization Beam Combiner; FPBS=Polarization Beam Splitter.

FPBC	-	NNNN	-	C	-	(C)	C	C	NN	-	CC/CCC
FPBS		<i>Center Wavelength</i>		<i>3rd Port Fiber</i>		<i>Package</i>	<i>Fiber Type</i>	<i>Fiber Sleeve</i>	<i>Fiber Length</i>		<i>Connector Type</i>
		1610~1610nm		S=S Type		M=Metal Box	2=PM1550Fiber	B= Bare fiber	05=0.5m		N=Without Connector
		1625~1625nm		P=P Type		Blank for SST	E=10/125 PMSC Fiber	L= Loose Tube	10=1.0m		FC/APC=FC/APC Connector
		1650~1650nm		Q=Q Type			T=12/130 PMDC Fiber	2= 2mm Cable	15=1.5m		LC/PC=LC/PC Connector
							G=25/300 PMDC Fiber	3= 3mm Cable	20=2.0m		SC/UPC=SC/UPC Connector