

1550nm PM Bandpass Filter (<10nm)

FEATURES

- High Isolation
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Metro Networks



SPECIFICATIONS

Parameters	Unit	Standard	High ER Type
Center Wavelength	nm	1550	
Min. Pass Band Width @ 0.5dB	nm	0.3, 0.7, 2.0, 3.0, 4.0, 5.0, 7.0	
Insertion Loss over Pass Band Wavelength	dB	≤1.0	≤1.2
Stop Band @ 25dB	0.3nm Bandwidth	1520~1549 & 1551~1610	
	0.7nm Bandwidth	1520~1548 & 1552~1610	
	2nm Bandwidth	1520~1547 & 1553~1610	
	3nm Bandwidth	1520~1546 & 1554~1610	
	4nm Bandwidth	1520~1545 & 1555~1610	
	5nm Bandwidth	1520~1544 & 1556~1610	
	7nm Bandwidth	1520~1543 & 1557~1610	
Configuration	D Type	-	2-port
	Y Type	-	3-port, (one-direction Blocked Wavelength Guide Out)
	X Type	-	4-port, (bi-direction Blocked Wavelength Guide Out)
Fiber Type at 3 rd or 4 th Port (for Y&X Type)	-	Same Fiber of other ports	
	-	Corresponding SM Fiber or 50/125um MM Fiber	
Optical Return Loss	dB	≥50	
Extinction Ratio	dB	≥20	≥22
Fiber Type	-	PM1550 Panda Fiber or 10/125um PMDC Fiber (O) 12/130um PMDC Fiber (T), 20/130um PMDC Fiber (Q) 25/250um PMDC Fiber (R) or 25/300um PMDC Fiber (G)	
Polarization Alignment	-	Slow Axis	
Fiber Tensile Load	N	5	
Maximum Optical Power (CW)	mW	300	
Operating Temperature	°C	0~70	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	(∅)5.5x35
	Metal Box	mm	(L)120x(W)12x(H)10

- Note:**
1. Specifications are for device without connectors; Specifications may change without notice.
 2. To add connectors, IL is 0.3dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 3. High ER type can only work in slow axis at pass port; Suggest to use Y or X type if blocked optical power is >1W.
 4. Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.

ORDERING INFORMATION (PN)

FPBP-NNNN	- NN	(C)	(C)	(C)	- (C)	C	C	NN	-CC/CCC
Center Wavelength	Bandwidth	Type	3rd Port Fiber	4th Port Fiber	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
1550=1550nm	03=0.3nm	R=High ER	Y=Same Fiber	Y=Same Fiber	M=Metal Box	2=PM1550Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	05=0.5nm	Blank for	S=Corr. SM Fiber	S=Corr. SM Fiber	Blank for SST	0=10/125 PMDC Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	20=2nm	Standard	5=50/125um Fiber	5=50/125um Fiber		T=12/130 PMDC Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	70=7nm		Blank for D Type	Blank for D&Y Type		G=25/300 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector