

1528nm Bandpass Filter for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters		Unit	Value
Center Wavelength		nm	1528
Min. Pass Band Width @ 0.5dB		nm	0.3, 0.7, 3.0
Insertion Loss over Pass Band Wavelength		dB	≤1.2
Stop Wavelength (ASE)	0.3nm Bandwidth	nm	1500~1527 & 1529~1600
	0.7nm Bandwidth	nm	1500~1526.5 & 1529.5~1600
	3nm Bandwidth	nm	1500~1524 & 1532~1600
Stop Wavelength (ASE)	Standard	dB	≥25
Isolation	High Isolation	dB	≥45
ASE Direction		-	F: Forward, B: Backward, T: Two-way
Configuration		-	D: 2-port, Y: 3-port, X: 4-port
Optical Return Loss		dB	≥50
Polarization Dependent Loss		dB	≤0.15
Fiber Type	Input&Output	-	SMF-28 Fiber or 10/130um DC Fiber NA=0.08 (O)
		-	10/130um DC Fiber NA=0.15 (O2) or 12/130um DC Fiber (T)
		-	25/250um DC Fiber (R) or 25/300um DC Fiber (G)
	ASE Guide Out (Y/X Type)	-	Same Fiber or MM Fiber
Fiber Tensile Load		N	5
Max. Average Optical Power (ASE+Signal)		W	0.3, 0.5, 1, 2, 3, 5, 10, 15, 20, 30, 50, 60, 80, 100
Max. Peak Power for pulse		kW	0.1, 1, 2, 3, 5, 10, 15, 20
Max. ASE Average Power		W	0.3, 0.5, 1, 2, 3, 4, 5, 10
Operating Temperature		°C	0~70
Storage Temperature		°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)
	Metal Box	mm	H: ^L 90x ^W 12x ^H 10 (>10W);M: ^L 120x ^W 12x ^H 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.3dB higher, RL is 5dB lower.
 - Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FFBP-1528-NN(C)(C)- (C) (C) - HNN P NN - (NN) -(C) (C) C NN -CC/CCC													
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Bwd ASE Fiber	Average Power	Peak Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type	
03-0.3nm	B-Backward	I-High	Y-Same Fiber	Y-Same Fiber	03-300mW	01-100W	1-1W	M-Metal Box	O-10/130 DC Fiber	B-Bare fiber	05-0.5m	N-Without Connector	
07-0.7nm	T-Two-way	Isolation	A-105/125um Fiber	A-105/125um Fiber	1-1W	1-1kW	5-5W	H-H Box	T-12/130 DC Fiber	L-Loose Tube	10-1.0m	FC/APC-FC/APC Connector	
30-3nm	Blank for Forward	Blank for	N=None	5-50/125um Fiber	5-5W	10-10kW	10-10W	Blank for SST	G-25/300 DC Fiber	2-2mm Cable	15-1.5m	LC/PC-LC/PC Connector	
	Standard	Blank for D Type	Blank for D Type	Blank for None or D Type	20-20W	20-20kW	Blank for 300mW		Blank for SMF-28 Fiber	3-3mm Cable	20-2.0m	SC/UPC-SC/UPC Connector	

