

1310nm High Power Multimode Bandpass Filter

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Laser Systems
- Research Labs



SPECIFICATIONS

Parameters		Unit	Value
Center Wavelength		nm	1310
Min. Pass Band Width @ 0.5dB		nm	2.0. 15
Insertion Loss over Pass Band Wavelength		dB	≤1.2
Stop Wavelength (ASE)	2nm Bandwidth	nm	1250~1307 & 1313-1430
	15nm Bandwidth	nm	1250~1298 & 1322-1430
Stop Wavelength (ASE)	Standard	dB	≥25
Isolation	High Isolation	dB	≥45
ASE Direction		-	F: Forward, B: Backward, T: Two-way
Configuration		-	D: 2-port, Y: 3-port, X: 4-port
Optical Return Loss		dB	≥30
Fiber Type	Input&Output	-	50/125um (OM2) or 62.5/125um (OM1) MM Fiber
			50/125um OM3 MM Fiber (3) or OM4 MM Fiber(4)
			105/125um MM Fiber, NA=0.12(D), 0.15(B), 0.22(A)
	ASE Guide Out (Y/X Type)	-	Same Fiber
Fiber Tensile Load		N	5
Max. Optical Power (CW, ASE+Signal)		W	1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 60, 80, 100
Max. ASE Optical Power (CW)		W	0.3, 0.5, 1, 2, 3, 4, 5, 10
Operating Temperature		°C	0~70
Storage Temperature		°C	-40~85
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)
	Metal Box	mm	H: ^L 90x ^W 12x ^H 10 (>10W);M: ^L 120x ^W 12x ^H 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.3dB higher, RL is 10dB lower.
 - Specifications are tested at low order modes.
 - Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FMBP-1310-NNN(C)(C)-(C) (C) - HPNN - (NN) - (C) C C NN - CC/CCC

Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Rev ASE Fiber	Optical Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
20~2nm	B=Backward	I=High	Y=Same Fiber	Y=Same Fiber	1~1W	1~1W	M=Metal Box	5= 50/125um MM Fiber	B= Bare fiber	05=0.5m	N=Without Connector
150~15nm	T=Two-way	Isolation	N=None	Blank for None or D Type	5~5W	5~5W	H=H Box	6= 62.5/125um MM Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	Blank for Forward	Blank for	Blank for D Type		10~10W	10~10W	Blank for SST	3= OM3 MM Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
		Standard			20~20W	Blank for 300mW		A= 105/125um, NA=0.22	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector
								B=105/125um, NA=0.15			

