

915~950nm High Power PBC/PBS

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Research Labs
- Laser Systems



SPECIFICATIONS

Parameter	Unit	Value	
Center Wavelength	nm	915, 930, 940, 950	
Bandwidth	nm	+/-15	
Insertion Loss	(Typ.)	dB	0.9
	(Max.)	dB	1.4
Directivity	dB	≥50	
Optical Return Loss	dB	≥45	
Extinction Ratio (for FPBS)	(Typ.)	dB	22
	(Min.)	dB	18
Fiber Type of Port 1 & Port 2	-	PM850 Fiber, PM980 Fiber or PM1060L Fiber (E) 10/125um PMDC Fiber (O) or 15/130um PMDC Fiber (W) 20/130um PMDC Fiber (Q) or 25/250um PMDC Fiber (R)	
Fiber Type of Port 3	S Type	-	Corresponding SM Fiber
	P Type	-	Same Fiber to Port1&2, Slow axis align to Port 1
	Q Type	-	Same Fiber to Port1&2, Slow axis is 45° to Port 1
Direction of Incident Polarization	-	Slow Axis	
Fiber Tensile Load	N	5	
Max. Optical Power (CW)	W	1, 2, 3, 5 10, 15, 20	
Operating Temperature	°C	0~50	
Storage Temperature	°C	-40~85	
Package Dimension	Stainless Steel Tube (SST)	mm	∅5.5x ^L 35 (≤5W); ∅6.0x ^L 50 (5~10W)
	Metal Box	mm	^L 90x ^W 12x ^H 10 (>10W); ^L 120x ^W 12x ^H 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.7dB higher, RL is 5dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and fiber type.

ORDERING INFORMATION (PN) FPBC=Polarization Beam Combiner; FPBS=Polarization Beam Splitter.

FPBC / FPBS	NNN <small>Center Wavelength</small>	C <small>3rd Port Fiber</small>	HP NN <small>Optical Power</small>	-(C) <small>Package</small>	C <small>Fiber Type</small>	C <small>Fiber Sleeve</small>	NN <small>Fiber Length</small>	- CC/CCC <small>Connector Type</small>
	915=915nm	S=S Type	1=1W	M=Metal Box	2=PM850Fiber	B= Bare fiber	05=0.5m	N=Without Connector
	930=930nm	P=P Type	5=5W	Blank for SST	H=PM980 Fiber	L= Loose Tube	10=1.0m	FC/APC=FC/APC Connector
	940=940nm	Q=Q Type	10=10W	or >10W	E=PM1060L Fiber	2= 2mm Cable	15=1.5m	LC/PC=LC/PC Connector
	950=950nm		20=20W		R=25/250 PMDC Fiber	3= 3mm Cable	20=2.0m	SC/UPC=SC/UPC Connector