C or L Band PM Cladding Power Stripper for Pulse Power

FEATURES

- High Input Optical Power
- Low Insertion Loss
- Epoxy-Free Optical Path
- High Reliability and Stability
- Low Profile Packaging

APPLICATIONS

- Fiber Laser
- Optical Amplifier
- High Power Laser
- Laser Source
- Test Equipment

SPECIFICATIONS

Parameter	Unit	Value
Pump Wavelength Range	nm	915, 950, 975, 980, 1480
Signal Wavelength Range	nm	1530~1580, 1570~1610
Fiber Type	-	8/125um NA=0.12(M), 6/125um NA=0.18(M1), 10/125um NA=0.075(O), 12/130um NA=0.2(T), 15/130um NA=0.075(W), 20/130um NA=0.075(Q), 25/250um NA=0.065(R), 25/300um NA=0.09(G), 25/400um NA=0.065(R1), 30/250um NA=0.06(R2), 30/400um NA=0.06(R3) or specified by customer
Signal Insertion Loss	dB	≤0.3
Signal Extinction Ratio	dB	≥16
Max. Stripped Pump Power	W	10, 30, 50, 100, 300, 500, 1000
Max. Signal Average Power	W	10, 50, 100, 200, 500, 1000, 2000
Max. Peak Power for Pulse	kW	0.1, 1, 2, 3, 5, 10, 15, 20, 50, 100
Strip Efficiency	%	≥98
Operating Temperature	°C	0~50
Storage Temperature	°C	-40~85
Package Dimension	mm	A: 65^{L}x12^{W}x8.6^{H}, B: 100^{L}x12^{W}x10^{H}
		C: 70^{L}x12^{W}x8^{H}, D: 100^{L}x15^{W}x10^{H}
		E: 150^{L}x25^{W}x10^{H}, F: 100^{L}x42^{W}x17^{H} (Water Cool)

Note: 1. Specifications are for device without connectors; Specifications may change without notice.
2. To add connectors, IL is 0.3dB higher, RL is 10dB lower, ER is 2dB Lower, Connector key is aligned to slow axis.
3. Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
4. Devices for higher optical power or with other type fiber or consigned fiber are also available.
5. Package size may be different for different fiber type, optical power and configuration.

ORDERING INFORMATION (PN)

PCTP - NN NN - C NN - (NNN) PNN - C C NN -CC/CCC

Pump Wavelength	*Signal Wavelength*	*Package*	*Pump Power*	*Signal Power*	*Peak Power*	*Fiber Type*	*Fiber Sleeve*	*Fiber Length*	*Connector Type*
91=915nm	15=1550nm	A=A Type	10=10W	100=100W	01=100W	O=10/125PMDC Fiber	B=Bare Fiber	05=0.5m	N=Without Connector
95=950nm	59=1590nm	B=B Type	50=50W	500=500W	1=1kW	Q=20/130PMDC Fiber		10=1.0m	FC/APC=FC/APC Connector
98=980nm		E=E Type	100=100W	1000=1000W	10=10kW	G=25/300PMDC Fiber		15=1.5m	SC/PC=SC/PC Connector
14=1480nm		F=F Type	1000=1000W	*Blank* for10W	100=100kW	R1=25/400PMDC Fiber		20=2.0m	LC/UPC=LC/UPC Connector
						M1=6/125PMDC Fiber			